

공업용 AE 센서

Industrial AE sensors

[ACOUSTIC EMISSION SENSORS]

| 모델명 | 주파수(kHz) | 감도 dB(0dB=1V/m/s) | 사용 온도 범위(°C) | 특징 | 중량*1 (gm) | 옵션 홀더 (P.44) |
|----------------|----------------|----------------------|-----------------|------------------|--------------|-----------------|
| 1045SWA | 200~1,300±10dB | 73±5 | -20~+80 | 앰프내장, 방수(IP×7)절연 | 65 | ⑤ ⑧ |
| 1045SWH | 250~1,000±6dB | 56±3 | -20~+200 | 내압방수(IP×8), 고온형 | 50 | ⑨ ⑩ |
| AE204SW | 200±20% | 66±3 | -20~+80 | 방수(IP×7)절연 | 41 | ① ⑥ ⑨ ⑩ |
| AE204SH150-BNC | 200±20% | (71±3) | -20~+150 | 고온형 | | ⑨ ⑩ |
| AE204DH | 200±20% | 71±3 | -20~+200 | 고온형 | 25 | ⑨ ⑩ |
| AE154DL | 150±20% | 68±3 | -196~+80 | 극저온형, 비절연 | 30 | - |

※ 1 : 케이블 제외.

